

## 5000 Series Fixtured Tools

- Rear & bottom exit available
- Standard Square Drive, Extended Ergo Drive or 1/4" Quick Change outputs available in most models
- Models available with 1/2" fixed sq. dr., 3/4" fixed sq. dr., and 2" sliding spindle



AEF35135A-2

2" Sliding Spindle, Rear Exit Model



AEF35135AB-2

2" Sliding Spindle, Bottom Exit Model



AEF35135AV

Extended Ergo Drive, Rear Exit Model



AEF35350A

Standard Spindle, Rear Exit Model



AEF35135AVB

Extended Ergo Drive, Bottom Exit Model

MODEL	FREE SPEED RPM	MAX TORQUE		OUTPUT DRIVE-IN	TORQUE RANGE		WEIGHT LESS SOCKET	
		Ft-lb	Nm		ft-lb	Nm	kg	lb

### 5000 Series

(V) = Extended Ergo Drive Output (VB) = Extended Output with Bottom Exit Cable (B) = Bottom Exit Cable

(-2) = 2" Sliding Spindle with Rear Exit Cable (B-2) = 2" Sliding Spindle with Bottom Exit Cable

AEF35075A (V) (VB) (-2) (B-2)	944	55	75	1/2 SQ. DR.	14 - 55	19 - 75	4.35	9.6
AEF35090A (V) (VB) (-2) (B-2)	767	66	90	1/2 SQ. DR.	17 - 66	23 - 90	4.35	9.6
AEF35110A (V) (VB) (-2) (B-2)	634	81	110	1/2 SQ. DR.	21 - 81	28 - 110	4.35	9.6
AEF35135A (V) (VB) (-2) (B-2)	515	100	135	1/2 SQ. DR.	25 - 100	34 - 135	4.35	9.6
AEF35170A (V) (VB)	418	125	170	1/2 SQ. DR.	32 - 125	43 - 170	4.35	9.6
AEF35170A (-2) (B-2)	418	125	170	3/4 SQ. DR.	32 - 125	43 - 170	4.35	9.6
AEF35280A*	236	207	280	3/4 SQ. DR.	52 - 207	70 - 280	6.17	13.6
AEF35350A*	192	258	350	3/4 SQ. DR.	65 - 258	88 - 350	6.17	13.6
AEF35420A*	159	310	420	3/4 SQ. DR.	77 - 310	105 - 420	6.17	13.6
AEF35515A*	129	380	515	3/4 SQ. DR.	95 - 380	128 - 515	6.17	13.6
AEF35635A*	104	469	635	3/4 SQ. DR.	117 - 469	159 - 635	6.17	13.6

\* Item 28843 is a panel mount 2" sliding spindle for 280 – 635 Nm models.