2-JAW ANGULAR GRIPPERS **SERIES GZ1000**

PRODUCT ADVANTAGES



"The top of the line"

Unique quality meets functionality

This is one of the best angular grippers on the market, enabling you to make your application more cost-effective and functional

Variable attachment

Decide for yourself whether you want use screws, locknuts or a toolkit clamping system for fastening

Sensing with process reliability

Unlike many other established products on the market, you can even differentiate between "Component present" and "Component not present"

SERIES CHARACTERISTICS

Installation size	Version		
GZ10XX	-01	-02	-03
Saw tooth jaw without query	•		
Saw tooth jaw with query		•	
Version for attaching customer-specific gripper fingers			•
2 million maintenance-free cycles (max.)	•	•	•
+ 🔐 Inductive sensor		•	
IP 30 IP30	•	•	•



BENEFITS IN DETAIL



- 1 Gripper jaw
 - available in different versions
- 2 Position sensing
 - via inductive proximity switch
- 3 Return spring
 - to open the gripper jaws
- 4 Mounting and positioning
 - via thread / through-hole
- (5) Drive
 - single-acting pneumatic cylinder
- 6 Housing
 - hard coated surface for increased durability
- 7 Mounting and positioning
 - via fit, thread and lock nut
- 8 Energy supply

► TECHNICAL DATA

	Stroke	Gripping force	Weight	IP class
Installation size	[°]	[N]	[kg]	
GZ1020	8	62	0,015 - 0,03	IP30
GZ1030	11	130	0,046 - 0,063	IP30
GZ1040	10	315	0,105 - 0,125	IP30

► FURTHER INFORMATION IS AVAILABLE ONLINE




All information just a click away at: www.zimmer-group.com. Find data, illustrations, 3D models and operating instructions for your installation size using the order number for your desired product. Quick, clear and always up-to-date.

2-JAW ANGULAR GRIPPERS **INSTALLATION SIZE GZ1020**

PRODUCT SPECIFICATIONS



Gripping force diagram



Forces and moments

Displays static forces and moments that can also have an effect, besides the gripping force.



Mr [Nm]	1
My [Nm]	0.6
Fa [N]	60

► INCLUDED IN DELIVERY



1 [piece] Locking nut C093610009

► RECOMMENDED ACCESSORIES



ENERGY SUPPLY



CONNECTIONS / OTHER



GVM5 Straight Fittings - Quick Connect Style



S8-G-3







CONNECTIONS / OTHER









Plug-in connector Straight Cable 5m - Socket M8 (female)



	Technical data		
Order no.	GZ1020-01	GZ1020-02	GZ1020-03
Stroke per jaw [°]	8	8	8
Gripper finger with integrated sensor	No	Yes	No
Gripping force in closing [N]	62	62	62
Closing moment [Nm]	0.5	0.5	0.5
Closing time [s]	0.01	0.01	0.01
Opening time [s]	0.02	0.02	0.02
Operating pressure min. [bar]	2	2	2
Operating pressure max. [bar]	6	6	6
Nominal operating pressure [bar]	6	6	6
Operating temperature min. [°C]	5	5	5
Operating temperature max. [°C]	+80	+80	+80
Air volume per cycle [cm³]	0.25	0.25	0.25
Weight [kg]	0.017	0.03	0.015

