

New





The Ingersoll Rand Revolution Series die grinders offer an outstanding combination of value and performance, delivering impressive comfort and durability with the power required for a wide range of service, maintenance and light production applications.

- Powerful motor delivers 0.30 kW (0.40 HP).
- 12 000 rpm free speed.
- Built-in lubricating wick optimizes the life of the angle gear set by improving lubrication to the bevel and pinion gear set.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- The low weight of this tool will reduce operator fatigue.
- Integral trigger safety lock prevents accidental tool start.
- Rear exhaust directs air away from the operator.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.

## Specifications at 6.2 bar (90 psi)

Part Number Ordering number Collet capacity Other available versions: - 14 000 rpm - 20 000 rpm

#### PERFORMANCE

Rated power Free speed

#### AIR SYSTEM

Air Inlet (NPTF) Minimum hose size Average air consumption Air consumption at load

### **NOISE & VIBRATION**

Sound pressure / power (ISO15744) Vibration level / measurement uncertainty (ISO28927)

WEIGHT & DIMENSIONS

Tool weight Tool length Height over spindle Shipping weight Shipping dimensions (L x W x H) UPC / EAN code Origin 312AC4A 45754595 1/4 in / 6 mm

> 314AC4A 320AC4A

0.40 HP / 0.30 kW 12 000 rpm

1/4 in 3/8 in / 10 mm 8.0 CFM / 3.8 L/s 32.0 CFM / 15.1 L/s

> 78.6 / 89.6 dB(A) 3.4 / 1.0 m/s<sup>2</sup>

1.21 lb / 0.55 kg 6.7 in / 170 mm 2.5 in / 64 mm 2.09 lb / 0.95 kg 193 x 116 x 63 mm 6 63023 08231 8 Made in China

CE

# www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.







Abrasives For the complete range, see our accessory catalogue.



**03A-MEDPD** 80398963 75 mm (3") backing pad, medium



**DG110-700-6MM** 04261053 Erickson collet, 6 mm





RG1-26 80227200 Collet body wrench

LG1-K284 80152119 Piped-away exhaust kit

33104-45



92938760 Hose whip, 1/4" NPT, 6 mm inside diameter, 45 cm (1.5 ft)

77NMC2 88104070 7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



For the complete range, see our accessory catalogue.

Filters, regulators, lubricators



**67-LBK1** 04637344 Lubricant kit for angle head tools



**67-4T** 04637336 Grease for high-speed angle heads



O2A-MEDPD<br/>8019896350 mm (2") backing pad, medium



DG110-700-G2 03641743 Erickson collet, 1/8" (3,2 mm)



DG110-700-G4 03641602 Erickson collet, 1/4" (6.35 mm)



**301-69** 04552683 Collet nut wrench



**IB6NMC2** 88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)

**Quick Release Couplings** 

For the complete range, see our accessory catalogue.



**10Z4** 03875671 Oil, Class 1, no. 10, 0.12 L



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

