




3arm° is a division of the Tecnospiro Machine Tool Company located in Sant Joan de Vilatorrada a small village about 40 miles west of Barcelona. They are a small family owned company that has been in business since the 60's. They have a state of the art manufacturing facility and a dynamic engineering staff that has been very innovative in design and inventing new products.


The 3arm ergonomic arm is the strongest most dependable arm available in the world market place today. It can be used for assistance in assembly, deburring, off line machining, and all types of lifting operations. Where ever operator fatigue is concern for employee safety, productivity, or quality 3arm has a solution.



3arm[®] MANIPULATOR M5



M5 with BRAKES




Manipulator M5 can be equipped with pneumatic brakes to completely lock all the axis of the arm allowing to move and lock in position the part or product to manipulate.

EXTENSIONS


Depending on the various needs of each application the arm can be supplied with a variety of extensions in order to increase the reach.

ACCESSORIES





Trolley+Lifter PNR (500mm)




Radial Extension 600mm (or 1 meter)

	Extension 600	Extension 1000	Trolley	Fix column	Lifter 500 PNR	Floor rail	Lifter Column 2000
Extension 600				•	•		
Extension 1000							
Trolley	•						
Fix column	•						
Lifter 500 PNR							
Floor rail							
Lifter Column 2000							

3arm Manipulator M5 offers a wide variety of configurations to move parts to and from conveyors, assembly lines, machine tools and much more up to 50 kg.

Being the lightest manually controlled load manipulator device with various quick change gripping systems (jaws, vacuum, magnet, hook or custom), the operator can work in excellent ergonomic and safety conditions while gaining an increase in productivity.



Pneumatic specifications

Supply fluid	Pressurized air	
Max. pressure of air supply	0.85 Mpa (8,5 bar)	
Max. working pressure	0.8 Mpa (8 bar)	
Maximum instantaneous	consumption	
	515 dM5/min	

Movements

ZX Plane	± 40°
Working radius in XY plane	1670 mm (65.7")
Z1 Axis	360°
Z2 Axis	180°
Z3 Axis	180°
X Axis	360°/4 x 90°
Vertical travel	707 mm (28")

Dimensions and weight

Height	339 mm (20.4")
Lenght	952 mm (59.1")
Width	262 mm (4.5")
Weight	39 Kg (66 lb)

Working conditions

Temperature	+15 a +45°C
Relative humidity	Max. 70%
Environment	Indoor industrial settings

Load capacity

Maximum net load, range	0-50Kg (0-110 lb)
Maximum net load	50 Kg (110 lb)
Maximum gross load (load	gripping system + load
to be manipulated)	62 Kg (136 lb)



CONNEXALL CO., LTD.

899/50 Moo 21, Soi Chongsiri Parkland, Bangphli-Yai,

Bangphli, Samutprakarn 10540 Thailand

E-mail: info@connexall.co.th

Phone: +66-2313-3400 Fax: +66-2313-3402



www.connexall.co.th